

HYDROSTOP

Hydrophilic Polymer Waterstop

PROPERTIES

HYDROSTOP is a hydrophilic polymer based waterstop, ultra thin profiled, re-swellable, polymer based on the latest Hybrid Technology to overcome problems commonly occurs with Bentonite based & PVC Waterstop during fixing & concrete pouring. HYDROSTOP is used for sealing purposes in civil engineering, structural engineering as well as tunneling for water pressure upto 5bar.

HYDROSTOP has a three dimensional polymer structure, which is build up from chemically resistant unstructured Polyurethane chains (macromolecules). The linkage of the polymer chains which is resistant to micro-bacterial attack.

The swelling ability happens due to hydrophilic polymer resin, which can expand in contact with water upto 750% to 800% from its original volume and have capacity to swell and shrink during repeated wet/dry cycles.

HYDROSTOP is safe and environmentally friendly material suitable for use in potable water tank, water retaining structures to used for sealing of construction joints, restoration of expansion joints, sealing of precast concrete segments, sealing of tubing part in tunneling, proofing of shafts and pipe penetrations.

Other Areas of Application:

- Water Tanks and Reservoirs
- Waste Water Treatment Structures
- Sewage Treatment Structures / Concrete Pipes
- Swimming Pools
- Cast in Place and Segmental Tunnels
- Dams
- Basements
- Marine Structures such as Dry Docks / Culverts
- Pile Caps / Secant Pile Walls

APPLICATION

Sealing of Construction Joints:

For the successful application of HYDROSTOP in construction joints, the profile has to be placed into the centre of the reinforcement or at least 10 cm away from the side exposed to water. It has multi installation option, adhered fully using primer and



can be nailed onto the concrete substrate. It has to be sure that the HYDROSTOP profile cannot change its position while concreting. The surface must be free from cavities, cracks, gravel pockets. The rough surfaces should be smoothed before priming or nailing of the profile.

TECHNICAL DATA

Storage:	Cool and dry in the original packaging up to 24 months
Color:	Blue (other colors available upon request)
Density:	Approx. 1.0 gr/cm ³
Hardness:	Approx. 38 (Shore A type)
Tensile strength:	Approx. 1.5 MPa - 2.1 MPa
Elongation:	Approx. 490 % - 770 %
Hydrostatic pressure:	>50m (5bar)
Swelling percentage:	Approx. 750 % - 800 % by volume
Swelling retarding:	Yes
Profile types:	Rectangle and Box profiles
Size:	5mm x 18mm;
Packaging:	7 x 15 Mtr. Coil / Carton (Other Packing also available)



STORAGE & SHELF LIFE

Store all material between 10 – 25 deg C in a cool, covered dry place. Do not expose the containers to direct sunlight and keep away from all sources of heat. In tropical climate conditions, the product has to be stored in an air-conditioned environment and protected from high humidity. The shelf life of the product is 24 months in unopened condition if stored as per the recommendations. Exposure to high temperature and humidity will result in considerable deterioration of the product and reduce its shelf life.

HEALTH & SAFETY

As with all construction chemical products caution should always be exercised whilst usage. Protective clothing such as gloves and goggles should be worn. Treat any splashes to the skin or eyes with fresh water immediately and seek medical advice. Should any of the product be accidentally swallowed do not induce vomiting, but call for medical assistance immediately.

For any further information please refer to the Material Safety Datasheet.

Manufactured By:

BPA-GmbH 



Under License:

PACIFIC
BUILDING SPECIALITY FZC

Ajman - United Arab Emirates.
E-mail: info@pacificbsgroup.com
www.pacificbsgroup.com